

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 March 2002 (28.03.2002)

PCT

(10) International Publication Number
WO 02/24829 A1

(51) International Patent Classification⁷: **C09K 5/04**

(21) International Application Number: **PCT/GB00/03596**

(22) International Filing Date:
19 September 2000 (19.09.2000)

(25) Filing Language: **English**

(26) Publication Language: **English**

(71) Applicant (for all designated States except US): **RHODIA ORGANIQUE FINE LIMITED** [GB/GB]; Oak House, Reeds Crescent, Watford, Hertfordshire WD1 1QH (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ROBERTS, Neil, Andre** [GB/GB]; Rhodia Organique Fine Limited, St. Andrew's Road, P.O. Box 46, Avonmouth, Bristol BS11 9YF (GB).

(74) Agent: **ELLIS-JONES, Patrick, George, Armine; J.A.** Kemp & Co., 14 South Square, Gray's Inn, London WC1R 5LX (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 02/24829 A1

(54) Title: **CENTRIFUGAL COMPRESSION REFRIGERANT COMPOSITIONS**

(57) Abstract: A liquid refrigerant composition is disclosed which comprises at least 35 % by weight of tetrafluoroethane and at least 20 % by weight of heptafluoropropane such that the sum of the concentrations of heptafluoroethane and heptafluoropropane is at least 90 % by weight of the composition.

CENTRIFUGAL COMPRESSION REFRIGERANT COMPOSITIONS

5

This invention relates to refrigerant compositions. More particularly, it relates to refrigerant compositions which can be used in place of R12 in a compression refrigeration system employing a centrifugal compressor.

R12 (CCl_2F_2) has been used for many years as a refrigerant composition.

10 However, in view of concerns over the use of CFC gases various attempts have been made to reduce or eliminate its use. In other words, ways have been sought to replace R12 by formulations which are not damaging to the environment.

One hydrocarbon which has been used with some success instead of R12 is tetrafluoroethane (R134). This is because it has a similar pressure-temperature
15 relationship and refrigerating effect to that of R12. Indeed in positive displacement compressors R134 is a good substitute for R12.

Unfortunately, it is not satisfactory to use R134 instead of R12 in systems involving the use of a centrifugal compressor. This is because an additional constraint is placed on the refrigerant in that, as well as having similar
20 thermodynamic properties, it must also have similar vapour density properties. Roughly, vapour densities are related to the molecular weight. The molecular weight of R12 is 121 whereas the molecular weight of R134 is only 102. This difference would require the dimensions of the impellor used in the centrifugal compressor system to be altered as well as its speed. Clearly there is a need for a composition
25 which can be used in an existing system without modification.

A further complication in the use of refrigerants using a centrifugal compressor resides in the fact that a centrifugal compressor uses a "flooded" evaporator i.e. some refrigerant liquid remains throughout the cooling cycle. As a result, the formulation of the liquid composition included in the system generally
30 differs from the formulation of the vapour circulating in the system.

The object of the present invention is to provide a refrigerant composition

-2-

which can be used in systems employing a centrifugal compressor without the need to modify the impellor dimensions or its speed. Clearly there is a need for a composition which can be used in an existing system without modification.

According to the present invention it has surprisingly been found that certain
5 liquid formulations of R134 and R227 (heptafluoropropane) behave well as replacements for R12 in centrifugal compression refrigerating systems. According to the present invention there is provided a liquid refrigerant composition which comprises at least 35% by weight of tetrafluoroethane and at least 20% by weight of heptafluoropropane such that the concentration of tetrafluoroethane and
10 heptafluoropropane is at least 90% by weight of the composition.

Tetrafluoroethane exists in two forms, namely the symmetrical 1,1,2,2-tetrafluoroethane and 1,1,1,2-tetrafluoroethane known as R134a. The latter is preferred for use in the present invention.

Likewise heptafluoropropane exists in two isomeric forms, namely
15 1,1,1,2,3,3,3-heptafluoropropane, known as R227ea which is preferred, and 1,1,1,2,2,3,3-heptafluoropropane, known as R227ca.

As indicated above the formulation in the vapour phase will differ from that in the liquid phase. It has been found that formulations comprising 20 to 52% by weight of R227 and, correspondingly, 80 to 48% of R134a will provide formulations
20 which will behave in the vapour phase in a manner similar to that of R12 with a variation of + or - 10%.

The preferred compositions of the present invention consist essentially of R134 and R227 (i.e. they are binary compositions), especially R134a and R227ea, but small amounts of a third component can be included. Any additional component
25 i.e. third or higher component can be present in an amount up to 10% weight, preferably up to 5%, and more preferably up to 2%, by weight of the composition. If more than one additional component is used then the total amount of these components is not more than 10% by weight. Since a principal aim of the formulation is to increase the overall molecular weight and thereby increase
30 the vapour density, it is more usual to replace some of the R134a than replace some

-3-

of the R227. Possible additional components include C318 (octafluorocyclobutane), R218 (octafluoropropane) and R125 (pentafluoroethane). The concentration of R134 is generally 80 to 35%, preferably 70 to 45% and more preferably 50 to 60%, by weight. The concentration of R227 is generally 20 to 65%, preferably 30 to 55% and especially 40 to 50%, by weight. A particularly preferred formulation consists of 52.5% of R134a and 47.5% of R227ea. This preferred formulation is based on the assumption that one needs to obtain a formulation which has an overall molecular weight corresponding to that of R12 i.e. 121. This is achieved with a vapour formulation of about 60% R134a and 40% R227ea.

10 However, as indicated above, molecular weight alone does not give a complete picture of how a formulation will behave in the vapour phase. It is also necessary for it to have the correct vapour density and vapour pressure characteristics.

Other preferred formulations have been found which attempt to take this into account; these contain less than or equal to 45% by weight of R227, especially 30 to 40, 42.5 or 45%, preferably 35 to 42.5 or 45% or 35 to 40%, by weight, the remainder being R134. A particularly preferred formulation comprises about 63.3% by weight of R134a and about 36.7% by weight of R227ea. These formulations are cheaper to make because R227ea is more expensive than R134a.

20 The present invention also provides a method of refrigerating a body which comprises placing the object in the vicinity of a refrigeration system which employs a centrifugal compressor wherein the liquid refrigerant supplied to the compressor is a composition of the present invention, and a refrigeration system incorporating a centrifugal compressor wherein the liquid in the compressor is a composition of the present invention.

25 The following Examples further illustrate the present invention:-

- 4 -

Blend	Composition / % w/w		Comments
	R134a	R227ea	
Example 1	52.5	47.5	Liquid phase composition
Example 2	60.0	40.0	Co-existing vapour phase of Example 1.
Example 3	63.3	36.7	Liquid phase composition
Example 4	68.0	32.0	Co-existing vapour phase of Example 3

Saturated Liquid Vapour Pressure Comparison

Temperature °C	Pressure / bar				
	R12	Example 1	Example 2	Example 3	Example 4
-20	1.510	1.306	1.359	1.282	1.292
-10	2.193	1.922	1.997	1.940	1.954
0	3.089	2.749	2.853	2.832	2.852
10	4.236	3.833	3.974	4.010	4.038
20	5.674	5.226	5.413	5.528	5.566
30	7.446	6.980	7.224	7.442	7.493
40	9.594	9.152	9.465	9.813	9.882

Comparison of Vapour Density.

Temperature °C	Vapour Density / kg/m ³		
	R12	Example 2	Example 4
-10	12.92	11.35	11.14
0	17.87	16.35	16.04
10	24.18	22.98	22.52
20	32.13	31.62	30.97
30	42.07	42.81	41.90
40	54.42	57.23	55.99

Refrigeration Performance

Temperature °C	R12		Example 2	
	Capacity/kW	COP	Capacity/kW	COP
-25	0.535	1.702	0.520	1.837
-20	0.734	1.983	0.704	2.101
-15	0.981	2.322	0.934	2.428
-10	1.274	2.718	1.210	2.817
-5	1.615	3.170	1.533	3.269
0	2.003	3.680	1.903	3.784
5	2.437	4.247	2.318	4.361

-5-

As can be seen, the formulations of Examples 2 and 4 give particularly good vapour pressure and vapour density values which are comparable to, or even better than, those of R12, especially at 30°C to 40°C which are generally the most important as these are the usual condensing temperatures.

-6-

CLAIMS

1. A liquid refrigerant composition which comprises at least 35% by weight of tetrafluoroethane and at least 20% by weight of heptafluoropropane such that the sum of the concentrations of heptafluoroethane and heptafluoropropane is at least 90% by weight of the composition.
2. A composition according to claim 1 which consists essentially of tetrafluoroethane and heptafluoropropane.
3. A composition according to claim 1 or 2 wherein the tetrafluoroethane is 1,1,1,2-tetrafluoroethane.
4. A composition according to claim 1 wherein the heptafluoropropane is 1,1,1,2,3,3,3-heptafluoropropane.
5. A composition according to claim 1 which consists essentially of 80 to 35% by weight of tetrafluoroethane and 20 to 65% by weight of heptafluoropropane.
6. A composition according to claim 5 which consists essentially of 70 to 45% by weight of tetrafluoroethane and 30 to 55% by weight of heptafluoropropane.
7. A composition according to claim 6 which consists essentially of 60 to 50% by weight of tetrafluoroethane and 40 to 50% by weight of heptafluoropropane.
8. A composition according to claim 1 which consists essentially of about 52.5% by weight of tetrafluoroethane and about 47.5% by weight of heptafluoropropane.
9. A composition according to claim 6 which comprises less than 45% by weight of heptafluoropropane.
10. A composition according to claim 9 which consists essentially of 35 to 45% by weight of heptafluoropropane.
11. A composition according to claim 9 which consists essentially of 35 to 40% by weight of heptafluoropropane.
12. A refrigeration system incorporating a centrifugal compressor wherein

-7-

the liquid in the compressor is a composition as claimed in claim 1.

13. A method of refrigerating a body which comprises placing the object in the vicinity of a refrigeration system which employs a centrifugal compressor wherein the liquid refrigerant supplied to the compressor is a composition as claimed
- 5 in claim 1.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/03596

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C09K5/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 92 17558 A (DU PONT) 15 October 1992 (1992-10-15) claims 1,8,15,22,23; examples 1-3 tables IV,V,VI	1,2,4-8, 12,13
X	WO 99 25786 A (ALLIED SIGNAL INC) 27 May 1999 (1999-05-27) claims 1-4,9; example 2; table IV	1,2,4-6, 9-13
X	WO 94 00529 A (GREAT LAKES CHEMICAL CORP.) 6 January 1994 (1994-01-06) page 3, line 2 - line 16; example 10	1-6,9, 12,13

☐ Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

13 June 2001

Date of mailing of the international search report

25/06/2001

Name and mailing address of the ISA
 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Puetz, C

INTERNATIONAL SEARCH REPORT
 Information on patent family members

Int. Application No

PCT/GB 00/03596

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9217558 A	15-10-1992	US 5182040 A	26-01-1993
		AU 652527 B	25-08-1994
		AU 1760892 A	02-11-1992
		BR 9205818 A	28-06-1994
		CA 2107232 A	29-09-1992
		DE 69225588 D	25-06-1998
		DE 69225588 T	10-09-1998
		EP 0577750 A	12-01-1994
		JP 6508825 T	06-10-1994
		KR 222635 B	01-10-1999
		US 5725791 A	10-03-1998
		US 5648017 A	15-07-1997
		US 5968406 A	19-10-1999
WO 9925786 A	27-05-1999	AU 1594099 A	07-06-1999
WO 9400529 A	06-01-1994	AU 4649593 A	24-01-1994
		CN 1083508 A	09-03-1994
		ZA 9304480 A	19-01-1994